



BASIC CONTROL SYSTEMS FOR DEPENDABLE SPREADING APPLICATIONS

The EZ Spread™ features the most reliable controls for basic spreading applications. Designed for granular and pre-wet applications, the EZ Spread electronic spreader control system from Cirrus combines core functionality with user-friendly operations.



EZ Spread
2- or 3-Channel Control

Product Summary

- Ground speed oriented or manual spreader control
- Includes 3 channels for 2- or 3-channel operation
- Open-loop control for auger, spinner and auxiliary (pre-wet, X-conveyor) channels
- Adjustable settings from 0-10
- Back lit control panel
- Programmable trim settings

Proportional Channels

- Independent control of 3 proportional channels
- Usually configured for auger/conveyor, spinner and either cross auger or pre-wet

Ground Speed Options

- Ground speed triggered (GST): on with truck motion, off with truck motion
- Ground speed oriented (GSO): on with truck, automatically adjusts output to compensate for truck speed, off when truck stops
- Manual: no ground speed interaction

Hydraulic Trimming

- Configuration mode for hydraulic trimming without manual trim pots

Blast & Pause

- Programmable blast included (on/off, timed)
- Use pause switch to pause spreading
- System powers up with pause active to prevent indoor spreading

Output Signal

- Multiple frequency settings for ease of valve compatibility

Power Safety

- Power Safe™ signal prevents random grounds powering any hydraulics system attached (auger, spinner, conveyor, etc.)
- Channel Safe™ detects and protects against open or short circuits on hydraulic drive channels

Operating Temperature Range

- Minimum: -20 degrees Celsius, Maximum: 70 degrees Celsius

Power Requirements

- Minimum: 11 Volts DC
- Maximum: 15 Volts DC
- Maximum: 10 Amps
- Internal fuse rated at 10 Amps



TRACKMATICS INC.
COVERING YOUR ASSETS

