



One efficient system for vehicle accessory control

The HammerHead™ 12-switch accessory control from Certified Cirus Control Systems provides a comprehensive control management system, compatibility with Windows® software and field configurable convenience.

PRODUCT SUMMARY

- Field configurable, programmable 12-switch accessory control panel
- Select from 7 switch types configured with any Windows® PC
- Switches can be re-programmed and labels re-printed on site
- Configuration software included with system

PRODUCT APPLICATION

- All types and sizes of truck chassis for mobile electronic and many hydraulic functions
- All-in-one accessory systems panel

PROGRAMMABLE SWITCH FUNCTIONS

- Momentary on/off: hold on, release off
- On/off: press on, press off
- Delayed on: hold on (delays for programmed time) before actuation, press again to turn off
- Delayed off: press to turn on for a programmed time (auto shut off)
- Default on: on at start up, press for off
- Default on/off: initial state is on when power is applied, on/off thereafter

COMBINATION CHOICES

- Mutually exclusive switches - one switch turns off up to 4 others
- Combination switches - one switch acts as master for up to 4 other switches
- 2-button guard - requires that two switches be pushed to actuate function
- Sequencing - series of switches linked in functional sequence; canceling the first switch automatically initiates the next switch in the sequence



HammerHead
accessory control



HammerHead
CPU

RELAY PROTECTION AND BREAKERS

- Each switch controls a relay and is protected by a 10-amp auto reset breaker

SWITCH CONFIGURATION UTILITY

- Works on any Windows® 2000 (or newer) computer

ELECTRONIC BACKPACK

- HammerHead system communicating on Certified Cirus Control Systems bus

SYSTEM MOUNTING

- Seat mounted or pedestal mounted
- Standalone, bracket mount

OPERATING TEMPERATURE RANGE

- Minimum: -20 degrees Celsius
- Maximum: 70 degrees Celsius

POWER REQUIREMENTS

- Minimum: 11 Volts DC
- Maximum: 15 Volts DC
- Maximum: 15 Amps
- Fuses rated at 10 Amps

